MH-3KW

Vertical Tubular Turbine Unit Main Technical Performance Parameters

Main Specifications				
Turbine				Remarks
Туре		MH-3K	W	
Rated Head	4m		-	Vertical Tubular
Rated Flow	136 l/s			Turbine
Power	3 KW			
Efficiency	60%			
Generator				Remarks
Туре		SF3-4	ŀ	
Rated Power	3KW			
Rated Voltage	230V			
Rated Current	13.04 A		Conforms to the	
Frequency	50Hz		IEC	
Rated Rotational	1500r/min		international	
Phase	1		electrician	
P.F.	0.9		committee	
Elevation	≤3000m			standard
Insulation Grade	B/B			& CE standard
Protection Grade	IP44			
Ambient Temperature	− 25 °C~+ 50 °C			
Relative Humidity	≤90%			
Control Panel				Remarks
Safety Protection	Short circuit Protection			
	Islanding Protection			
	Over Load Protection			
	Grounding Fault Protection			
Packing Material	Fiberboard			
Packing Size	1.2 M3			
Packing Weight	Net	Kg	420	
	Gross	Kg	450	

Stated: This product presents or the technical parameter revision is the technical improvement result, no other explanation.

Note: The modification of the product appearance or technical parameters, which is a result of technique improvement, will not be announced additionally.