


Micro-Hydro-Turbine-Power-Single-Dual-nozzle- CJD-6KW Main Parameters				
Water Turbine				
No.	Items	Parameters		Remarks
1	Model	CJD-6KW		Dual Nozzle Turgo Turbine
2	Rated Head	18--20	(meters)	
3	Rated Flow	38--50	(l/s)	
4	Output	6000	(W)	
5	Efficiency	70	(%)	
6	Pipe Diameter	200	(mm)	
Generator				
No.	Items	Parameters		Remarks
1	Model	SF6.0-4		 Rear Earth Permanent Magnet Generator
2	Style	PMG		
3	Output	6000	(W)	
4	Voltage	230	(V)	
5	Current	26.08	(A)	
6	Frequency	50	(HZ)	
7	Rotary Speed	1500	(RPM)	
8	Phase	Single	(Phase)	
9	Power Factor	1.0		
10	Altitude	≤3000	(meters)	
11	Insulation Grade	B / B		
12	Protection Grade	IP44		
13	Temperature	-25~+50	°C	
14	Relative Humidity	≤90	%	
Control Box / Control Panel				
No.	Items	Parameters		Remarks
1	Model	WY6.0-1		
2	Safety Protection	Short circuit Protection		
3		Islanding Protection		
4		Over Load Protection		
5		Grounding Fault Protection		
Packing				
No.	Items	Parameters		Remarks
1	Packing Material	Fiberboard		
2	Packing Size	105×75×77	(CM)	
3	Net Weight		(KGS)	
4	Gross Weight	255	(KGS)	
Note: The modification of the product appearance or technical parameters, which is a result of technique improvement, will not be announced additionally.				