

DLLD Micro Hydro Syetm Conventional Models

No.	Model	Head (m)	Flow	Generator	Phase	Speed	Pipe Diamter	Gross Weight	Referenbce EXW Price
			(m3/s)	(W)		(rpm)	(mm)	(Kg)	(USD)
1	XJ14-0.3DCT4-Z	12/14	0.003-0.005	300	Single	1500	50	20	600
2	XJ18-0.5DCT4-Z	12/18	0.005-0.007	500	Single	1500	50-75	23	800
3	XJ18-0.75DCT4-Z	14-18	0.005-0.008	750	Single	1500	75	42	1,053
4	XJ22-1.1DCT4-Z	16-22	0.008-0.010	1100	Single	1500	100	76	2,069
5	XJ22-1.1DCTH-Z	15	0.010-0.015	1100	Single	1500	125-150	120	2,320
6	XJ25-1.5DCT4-Z	18-25	0.008-0.011	1500	Single	1500	125	76	2,213
7	XJ25-1.5DCTH4-Z	15	0.012-0.018	1500	Single	1500	125-150	120	2,482
8	XJ25-3.0DCT4-Z	25-35	0.015-0.019	3000	Single	1500	125-150	102	3,544
9	XJ25-3.0DCFF4-Z	18-20	0.018-0.030	3000	Single	1500	150	134	3,885
10	XJ28-6.0DCT4/6-Z	28-35	0.030-0.038	6000	Single	1500	150-200	210	7,410
11	XJ28-6.0DCFF4/6-Z	18-20	0.038-0.050	6000	Single	1000	200	260	7,729
12	XJ30-10DCT4/-Z	30-38	0.040-0.050	10000	Single	1500	200-250	300	12,590
13	XJ30-10DCTF4/6-Z	25-30	0.050-0.060	10000	Single	1000	200-250	320	12,992
14	XJ30-12SCTF4/-Z	28-35	0.050-0.060	12000	Three	1500	200-250	325	15,129
15	XJ30-15SCTF4/6-Z	30-40	0.060-0.070	15000	Three	1500/1000	200	350	16,619
16	XJ30-20SCTF4/6-Z	30-45	0.060-0.100	20000	Three	1500/1000	250-300	380	22,158
17	XJ38-30SCTF4/6-Z	38-45	0.090-0.120	30000	Three	1500/1000	250-300	660	31,654
18	ZD1.8-0.3DCT1 Z	1.8	0.04	300	Single	1500	50	31	738
19	ZD2.0-0.5DCT4-Z	2	0.045	500	Single	1500	50	31	929
20	ZD2.2-0.7DCT1 Z	2.2	0.05	700	Single	1500	50	36	1,000
21	ZD2.5-1.0DCT1 Z	2.5	0.05	1000	Single	1500	50	43	1,167
22	DG12-3.0DCT4-Z	11	0.045	3000	Single	1500	150	140	4,685
23	GD15-LZ-3KW	7	0.09	3000	Single	1000	200	306	6,224
24	GD20-LZ-6KW	7	0.156	6000	Single	1500	300		9,352
25	GD20-LZ-10KW	11	0.165	10000	Single	1500	300		12,230
26	GD30-LZ-15KW	5--7	0.352	15000	Single	1500	500		23,989
27	GD30-LZ-20KW	7--9	0.38	20000	Single	1500	500		31,662
28	GD35-LZ-30KW	9	0.55	30000	Single	1500	600		45,952

Remark:

1. Model name clarification : XJ means Turgo, ZD means Propeller, DG means Tubular, D means single phase, S means 3 phase, C means PMG, T means synchronous generator, 4/6 means generator poles, Z means steady voltage regulator;
2. The EXW price is only for reference excluding the delivery cost, it should request the official quotation beofre placing the order and would subject to adjust the price based on the raw materials and exchange rate flotes.
3. The above selection is only for conventional models, we could custom make kinds of models based on specific site condition, and also speicail voltage and frequency;
4. The reference prie including the electronic automatic voltage regulator and export fibre packaging, excluding the pipe and installation cost.
5. The above data is copyright by DLLD Power and any other party should not be used for any other commercial promotion before approved.